

StanSolv AF-15

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Interior finish** Flocked
- **Exterior finish** Embossed texture
- **Length (inches)** 12
- **Thickness (inches)** 0.015 (15 mil)
- **Colour/Color** Green
- **Wrist** Straight cuff
- **Size** 7 8 9 10 11
- **Packaging** 12 pairs/bag - 72 pairs/carton



PERFORMANCE RESULTS

Certification category 3

CE 0334



4101



JKL



Legends



**MECHANICAL
HAZARDS
EN 388**

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4

— Puncture resistance
— Tear resistance
— Blade cut resistance
— Abrasion resistance



**LOW CHEMICAL
PROTECTION
EN 374**



**MICRO-ORGANISMS
EN 374**



**RADIOACTIVE
CONTAMINATION
EN 421**



**SPECIFIC CHEMICAL
PROTECTION
EN 374**

Letter Chemical
Code product

A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofuran
I	Ethyl acetate
J	n-heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS
EN 511**

PERFORMANCE LEVELS

0-4 0-4 0 or 1

— Water permeability
— Contact cold resistance
— Convective cold resistance



**HEAT
AND FIRE
EN 407**

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4

— Resistance to large quantities of molten metal
— Resistance to small drops of molten metal
— Radiant heat resistant
— Convective heat resistance
— Contact heat resistance
— Burning behaviour

For more details : www.mapa-pro.com

MAPA
PROFESSIONAL
www.mapa-pro.com

SPECIFIC ADVANTAGES

- Excellent dexterity, for handling small objects
- Good grip on slippery objects, due to the embossed exterior finish
- Flock lining provides comfort and absorbs perspiration

MAIN FIELDS OF USE

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- Persons sensitized to dithiocarbamates and thiazoles should not use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

- Store the gloves in their original packaging protected from light, humidity and heat.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (alcohols, diluents, etc.) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves in use with under running water, and rub over with a dry cloth
- Caution : improper use of the gloves or submitting them to any cleaning or laundering process which is not specifically recommended can alter their performance levels.

Drying conditions

- Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

- This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.

This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate 0072/014/162/04/06/0029
- Issued by the notified body nr 0072
I.F.T.H. – Av. Guy de Collongue - F-69134 ECULLY CEDEX